



ALLIANCE PLAST

TECHNICAL DATA SHEET

✉ info@allianceplast.com

☎ +371 28 664 102

📍 Lubanas str. 125a-18, Riga, LV-1021, Latvia

🌐 www.allianceplast.com



Shape:	RECTANGULAR
Volume:	5870 ml
External top with lid:	287,2x194 mm
External bottom:	253,4x160,2 mm
External lid:	281,4x188,2 mm
Height container with lid:	151,3 mm
Height lid:	12 mm
Weight container:	158 g
Weight standard lid:	50 g
Weight standard handle:	42 g



ARTICLE: AL293X198/5,8

OPEN

Closure type:	Snap-On	Tamper Evidence type:	Slider
Protective collar:	Yes	Lid type options:	Standard



Handle available:	None
-------------------	------

Different IML options

Perfect colour matching



Decoration available:

Container

Lid

IML

Yes

Yes

HANDLE
OPTION



Full cover

Peek inside
Create a transparent
pot window



Perfect mix
Clear pot with colourful
lid. Or vice versa



Coloured
plastic options



Choose from Pantone
or mixed CMYK
colour palettes



Raw material options:

PP random QU 80 A (MFI 35), Braskem (MFI 40), Borealis RJ377MO Random, Moplen RP348T, Borealis BD950MO FreezeGrade (Transparent).

Masterbatch colors:

Preferred colours: White 101, Clear, Natural, Blue 201, Dark Blue 204, Black 601, Light Grey 502, Red 331, Yellow 430 and Green 803. Additional colours: Transparent Red 338, Silver 521, Gold 21720, Warm Red 307, Warm Yellow 417, Beige 421, Brown 901, Dark Grey 501 (metal grey), Orange 741 and Blue 213. All other colours on request.

Approvals:

All products comply with the FDA and European legislation in force relating to materials and articles intended to come into contact with food.



Stackability, filled:

kg (=max weight on bottom container)

The stacking tests have been performed with the standard raw material as stated above at 23° C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of free-standing stacking and transportation. Notably, transparent (CLX) materials are softer than standard material, hence stacking must be considered when contact clear materials are chosen.



Packed in plastic sleeves

Total Pcs. Per PALETTE

PALLET type, mm

LIDS + CUPS	CUPS	LIDS
N/A	1200	4800
1200x1000	1200x800	1200x800
Height 2.65m (packed in sleeves)		



Hot filling:

85–95° C

The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling.

After cooling of the product and pail, the pail regains its original stacking strength.



Cold temperatures:

The standard resin material for white/coloured products resists temperatures down to -20° C. Deep freezing below -20° C may require a special resin available on request. Standard transparent (CLX) products might become brittle at temperatures below 0° C, and special resins are available on request for applications below freezing. Resins tailored for freezing stability has a lower stackability than standard resin which must be taken into consideration.

Microwave safe



Special:

The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage.

Shelf life:



Quality information:

Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) on a rolling 12 months basis are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.



UN approval:

No



ALLIANCE PLAST

TECHNICAL DATA SHEET



✉ info@allianceplast.com

☎ +371 28 664 102


📍 Lubanas str. 125a-18, Riga, LV-1021, Latvia

🌐 www.allianceplast.com

LABEL PRINT AREA




DIMMENSIONS




PALLETIZATION

For items that are packed in boxes



STICKER ON THE BOX



1. Description (Eng)
2. Article (Eng)
3. Production date
4. Pieces per BOX
5. Customer and Order nr.
6. Customer Order Defined EAN-13 Barcode
7. Article Code (4 digit)