



TECHNICAL DATA SHEET

info@allianceplast.com

info@allianceplast.com

+371 28 664 102

Q Lubanas str. 125a-18, Riga, LV-1021, Latvia

www.allianceplast.com



Shape: ROUND Volume: 22420 ml External diameter top with lid: 340 mm External diameter bottom: 284,6 mm External diameter lid: 335.1 mm Height container with lid: 332.3 mm Height lid: 15 mm Weight container: 562 g Weight standard lid: 131 g



ARTICLE: AL340/20,5H



Weight standard handle:

Slider Tamper Evidence type: Lid type options: Standard

Different IML options



Perfect colour matching







Lid

Decoration available: Containe

Closure type:

Protective collar:

Handle available:

IMI No







PP random QU 80 A (MFI 35), Braskem (MFI 40), Borealis RJ377MO Random, Moplen RP348T, Borealis BD950MO



Choose from Pantone or mixed CMYK colour palettes

PANTONE



Raw material options:

Freezgrade (Transparent). Masterbatch colors:

Preferred colours: White 101, Clear, Natural, Blue 201, Dark Blue 204, Black 601, Light Grey 502, Red 331, Yellow 430 and Green 803. Additional colours: Transparent Red 338. Silver 521. Gold 21720. Warm Red 307, Warm Yellow 417, Beige 421, Brown 901, Dark Grey 501 (metal grey), Orange 741 and Blue 213. All other

Snap-On

Plastic/ Metal

Yes

All products comply with the FDA and European legislation in force relating to materials and articles intended to come into contact with food.

Approvals:




kg (=max weight on bottom container)

The stacking tests have been performed with the standard raw material as stated above at 23° C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to dertermine the viability of free-standing stacking and transportation. Notably, transparent (CLX) materials are softer than standard material, hence stacking must be considered when contact clear materials are chosen.







LIDS + CUPS	CUPS	LIDS
-	540	2400
-	1100x1300	1200x800
Height 2.65m		



Hot filling:

85-95° C

The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling.

After cooling of the product and pail, the pail regains its original stacking strength.

The standard resin material for white/coloured products resists temperatures down to -20° C. Deep freezing below -20° C may require a special resin available on request. Standard transparent (CLX) products might become brittle at temperatures below 0° C, and special resins are available on request for applications below freezing. Resins tailored for

freezing stability has a lower stackability than standard resin which must be taken into consideration.



Special:

Shelf life:

Microwave safe

The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage.

Quality information:

Cold temperatures:

Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) on a rolling 12 months basis are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.



UN approval:

No



ALLIANCE PLAST


TECHNICAL DATA SHEET


✓ info@allianceplast.com


\ +371 28 664 102

Q Lubanas str. 125a-18, Riga, LV-1021, Latvia

www.allianceplast.com







- 1. Description (Eng)
- 2. Article (Eng)
- 3. Production date
- 4. Pieces per BOX
- 5. Customer and Order nr.
- 6. Customer Order Defined EAN-13 Barcode
- 7. Article Code (4 digit)